



## ■ MODEL AND SUFFIX CODES

For EJXC40A Remote Digital Sensor, please refer to GS 01C25W05-01EN.

| Model                      | Suffix Codes                                                                                      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                   |           |        |              |                     |            |                     |                     |                     |
|----------------------------|---------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|-----------|--------|--------------|---------------------|------------|---------------------|---------------------|---------------------|
| EJX610A<br>EJX630A         | .....<br>.....                                                                                    | Absolute pressure transmitter<br>Gauge pressure transmitter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                   |           |        |              |                     |            |                     |                     |                     |
| Output signal              | -D .....<br>-E .....<br>-J .....<br><br>-F .....<br>-G .....                                      | 4 to 20 mA DC Output with digital communication (BRAIN protocol)<br>4 to 20 mA DC Output with digital communication (HART 5 protocol)<br>4 to 20 mA DC with digital communication (HART 5 / HART 7 protocol)<br>(Refer to GS 01C25T01-01EN)<br>Digital communication (FOUNDATION Fieldbus protocol, refer to GS 01C25T02-01EN)<br>Digital communication (PROFIBUS PA protocol, refer to GS 01C25T04-01EN)                                                                                                                                                                                               |                   |           |        |              |                     |            |                     |                     |                     |
| Measurement span (capsule) | A. ....<br>B. ....<br>C. ....<br>D. ....                                                          | 2 to 200 kPa (0.3 to 29 psi)<br>0.01 to 2 MPa (1.5 to 290 psi)<br>0.05 to 10 MPa (7.3 to 1450 psi)<br>0.35 to 70 MPa (50.8 to 10150 psi)                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                   |           |        |              |                     |            |                     |                     |                     |
| Wetted parts material *2   | S. ....<br>H. ....                                                                                | <table> <tr> <th>Process connector</th><th>Diaphragm</th><th>Others</th></tr> <tr> <td>316L SST *9#</td><td>Hastelloy C-276 *1#</td><td>316L SST #</td></tr> <tr> <td>Hastelloy C-276 *1#</td><td>Hastelloy C-276 *1#</td><td>Hastelloy C-276 *1#</td></tr> </table>                                                                                                                                                                                                                                                                                                                                    | Process connector | Diaphragm | Others | 316L SST *9# | Hastelloy C-276 *1# | 316L SST # | Hastelloy C-276 *1# | Hastelloy C-276 *1# | Hastelloy C-276 *1# |
| Process connector          | Diaphragm                                                                                         | Others                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                   |           |        |              |                     |            |                     |                     |                     |
| 316L SST *9#               | Hastelloy C-276 *1#                                                                               | 316L SST #                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                   |           |        |              |                     |            |                     |                     |                     |
| Hastelloy C-276 *1#        | Hastelloy C-276 *1#                                                                               | Hastelloy C-276 *1#                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                   |           |        |              |                     |            |                     |                     |                     |
| Process connections        | 4 .....<br>7 .....<br>8 .....<br>9 .....                                                          | 1/2 NPT female<br>1/2 NPT male<br>G1/2 DIN 16 288 male *3<br>M20×1.5 DIN 16 288 male *3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                   |           |        |              |                     |            |                     |                     |                     |
| —                          | N. ....                                                                                           | Always N                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                   |           |        |              |                     |            |                     |                     |                     |
| —                          | -0 .....                                                                                          | Always 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                   |           |        |              |                     |            |                     |                     |                     |
| Amplifier housing          | ▶ 1 .....<br>3 .....<br>2 .....                                                                   | Cast aluminum alloy<br>Cast aluminum alloy with corrosion resistance properties *4<br>ASTM CF-8M stainless steel *5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                   |           |        |              |                     |            |                     |                     |                     |
| Electrical connection      | ▶ 0 .....<br>2 .....<br>4 .....<br>5 .....<br>7 .....<br>9 .....<br>A. ....<br>C. ....<br>D. .... | G1/2 female, one electrical connection without blind plugs<br>1/2 NPT female, two electrical connections without blind plugs<br>M20 female, two electrical connections without blind plugs<br>G1/2 female, two electrical connections with a blind plug*6<br>1/2 NPT female, two electrical connections with a blind plug*6<br>M20 female, two electrical connections with a blind plug*6<br>G1/2 female, two electrical connections and a 316 SST blind plug<br>1/2 NPT female, two electrical connections and a 316 SST blind plug<br>M20 female, two electrical connections and a 316 SST blind plug |                   |           |        |              |                     |            |                     |                     |                     |
| Integral indicator         | ▶ D. ....<br>E. ....<br>N. ....                                                                   | Digital indicator *7<br>Digital indicator with the range setting switch (push button) *8<br>(None)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                   |           |        |              |                     |            |                     |                     |                     |
| Mounting bracket           | ▶ L. ....<br>N. ....                                                                              | 316 SST 2-inch pipe mounting<br>None                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                   |           |        |              |                     |            |                     |                     |                     |
| Optional Codes             |                                                                                                   | □/ Optional specification                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                   |           |        |              |                     |            |                     |                     |                     |

The “▶” marks indicates the most typical selection for each specification. Example: EJX630A-DAS4N-012NN/□.

\*1: Hastelloy C-276 or ASTM N10276.

\*2: ⚠ Users must consider the characteristics of selected wetted parts material and the influence of process fluids. The use of inappropriate materials can result in the leakage of corrosive process fluids and cause injury to personnel and/or damage to plant facilities. It is also possible that the diaphragm itself can be damaged and that material from the broken diaphragm and the fill fluid can contaminate the user's process fluids.  
Be very careful with highly corrosive process fluids such as hydrochloric acid, sulfuric acid, hydrogen sulfide, sodium hypochlorite, and high-temperature steam (150°C [302°F] or above). Contact Yokogawa for detailed information of the wetted parts material.

\*3: Not applicable for combination of capsule code D and wetted parts material code H. Threads are based on the withdrawn DIN 16 288.

\*4: Not applicable for electrical connection code 0, 5, 7, 9 and A.

\*5: Not applicable for electrical connection code 0, 5, 7 or 9.

\*6: Material of a blind plug; aluminum alloy for code 5 and 9, and SUS304 for code 7.

\*7: Not applicable for output signal code G.

\*8: Not applicable for output signal code F.

\*9: Intergranular corrosion test passed according to ASTM A262 Practice E.

The #marks indicate the construction materials conform to NACE material recommendations per MR0175/ISO 15156. Please refer to the latest standards for details. Selected materials also conform to NACE MR0103.

## ■ OPTIONAL SPECIFICATIONS (For Explosion Protected type) “◇”

For other agency approvals and marine approvals, please refer to GS 01C25A20-01EN.

Please select appropriate equipment in accordance with the laws and regulations of the relevant country/region, when it is used in a location where explosive atmospheres may be present.

| Item                | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Code |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| Factory Mutual (FM) | FM Explosionproof Approval *1<br>Applicable Standard: FM3600, FM3615, FM3810, NEMA 250, ANSI/UL 61010-1, ANSI/UL 61010-2-30<br>Explosionproof for Class I, Division 1, Groups B, C and D, Dust-ignitionproof for Class II/III, Division 1, Groups E, F and G, in Hazardous locations, indoors and outdoors (Enclosure: Type 4X)<br>“FACTORY SEALED, CONDUIT SEAL NOT REQUIRED.”<br>Temperature class: T6, Amb. Temp.: -40 to 60°C (-40 to 140°F)                                                                                                                                                                                                                                                                                                                                                         | FF1  |
|                     | FM Intrinsically safe Approval *1*2<br>Applicable Standard: FM 3600, FM 3610, FM 3611, FM 3810, ANSI/ISA-60079-0, ANSI/ISA-60079-11, ANSI/ISA-61010-1, NEMA 250<br>Intrinsically Safe for Class I, Division 1, Groups A, B, C & D, Class II, Division 1, Groups E, F & G and Class III, Division 1, Class I, Zone 0, in Hazardous Locations, AEx ia IIC Nonincendive for Class I, Division 2, Groups A, B, C & D, Class II, Division 2, Groups F & G, Class I, Zone 2, Group IIC, in Hazardous Locations<br>Enclosure: Type 4X, Temp. Class: T4, Amb. Temp.: -60 to 60°C (-75 to 140°F)<br>Intrinsically Safe Apparatus Parameters<br>[Groups A, B, C, D, E, F and G] Vmax=30 V, Imax=200 mA, Pmax=1 W, Ci=6 nF, Li=0 µH<br>[Groups C, D, E, F and G] Vmax=30 V, Imax=225 mA, Pmax=1 W, Ci=6 nF, Li=0 µH | FS1  |
|                     | Combined FF1 and FS1 *1*2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | FU1  |
| ATEX                | ATEX Flameproof Approval *1<br>Applicable Standard: EN IEC 60079-0, EN 60079-1, EN 60079-31<br>Certificate: KEMA 07ATEX0109 X<br>II 2 G Ex db IIC T6...T4 Gb, II 2 D Ex tb IIC T85°C Db<br>Degree of protection: IP66/IP67<br>Amb. Temp. (Tamb) for gas-proof:<br>T4: -50 to 75°C (-58 to 167°F), T5: -50 to 80°C (-58 to 176°F), T6: -50 to 75°C (-58 to 167°F)<br>Process Temp. for gas-proof (Tp):<br>T4: -50 to 120°C (-58 to 248°F), T5: -50 to 100°C (-58 to 212°F), T6: -50 to 85°C (-58 to 185°F)<br>Max. surface Temp. for dust-proof: T85°C (Tamb: -30 to 75°C, Tp: -30 to 85°C) *3                                                                                                                                                                                                            | KF22 |
|                     | ATEX Intrinsically safe Approval *1*2<br>Applicable Standard: EN IEC 60079-0, EN 60079-11<br>Certificate: DEKRA 11ATEX0228 X<br>II 1 G Ex ia IIC T4 Ga, II 2 D Ex ia IIC T85°C T100°C T120°C Db<br>Degree of protection: IP66/IP67<br>Amb. Temp. (Tamb) for EPL Ga: -50 to 60°C (-58 to 140°F)<br>Maximum Process Temp. (Tp) for EPL Ga: 120°C<br>Electrical data: Ui=30 V, Ii=200 mA, Pi=0.9 W, Ci=27.6 nF, Li=0 µH<br>Amb. Temp. for EPL Db: -30 to 60°C *3<br>Max. surface Temp. for EPL Db: T85°C (Tp: 80°C), T100°C (Tp: 100°C), T120°C (Tp: 120°C)                                                                                                                                                                                                                                                 | KS21 |
|                     | Multiple types of protection (KF22, KS21 or Intrinsically safe Ex ic) *1*2<br>Applicable Standard: EN IEC 60079-0, EN 60079-11<br>II 3 G Ex ic IIC T4 Gc, Amb. Temp.: -30 to 60°C (-22 to 140°F) *3<br>Ui=30 V, Ci=27.6 nF, Li=0 µH                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | KU22 |

| Item                                 | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Code |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| Canadian Standards Association (CSA) | <p>CSA Explosionproof Approval *1</p> <p>Certificate: 2014354</p> <p>Applicable Standard: C22.2 No. 25, C22.2 No. 30, CAN/CSA-C22.2 No. 94, CAN/CSA-C22.2 No. 61010-1, CAN/CSA-C22.2 No. 61010-2-030, CAN/CSA-C22.2 No. 60079-0, CAN/CSA-C22.2 No. 60079-1, CAN/CSA-C22.2 No. 60529</p> <p>Explosion-proof for Class I, Groups B, C and D.</p> <p>Dustignition-proof for Class II/III, Groups E, F and G.</p> <p>When installed in Division 2, "SEAL NOT REQUIRED" Enclosure: Type 4X,</p> <p>Temp. Code: T6...T4</p> <p>Ex d IIC T6...T4 Enclosure: IP66/IP67</p> <p>Max.Process Temp.: T4;120°C(248°F), T5;100°C(212°F), T6; 85°C(185°F)</p> <p>Amb.Temp.: -50 to 75°C(-58 to 167°F) for T4, -50 to 80°C(-58 to 176°F) for T5, -50 to 75°C(-58 to 167°F) for T6 *3</p> <p>Process Sealing Certification</p> <p>Dual Seal Certified by CSA to the requirement of ANSI/ISA-12.27.01</p> <p>No additional sealing required</p> <p>Primary seal failure annunciation: at the zero adjustment screw</p>                                                                                                                                                                                                                                                                                                                                                                                   | CF1  |
|                                      | <p>CSA Intrinsically safe Approval *1*2</p> <p>Certificate: 1606623</p> <p>[For Division System]</p> <p>Applicable Standard: C22.2 No.0, C22.2 No.94, C22.2 No.157, C22.2 No.213, C22.2 No.61010-1, C22.2 No.61010-2-030</p> <p>Intrinsically Safe for Class I, Division 1, Groups A, B, C &amp; D, Class II, Division 1, Groups E, F &amp; G, Class III, Division 1, Nonincendive for Class I, Division 2, Groups A, B, C &amp; D, Class II, Division 2, Groups F &amp; G, Class III, Division 1</p> <p>Enclosure: Type 4X, Temp. Code: T4 Amb. Temp.: -50 to 60°C(-58 to 140°F) *3</p> <p>Electrical Parameters: [Intrinsically Safe] Vmax=30V, Imax=200mA, Pmax=0.9W, Ci=10nF, Li=0 µH</p> <p>[Nonincendive] Vmax=30V, Ci=10nF, Li=0 µH</p> <p>[For Zone System]</p> <p>Applicable Standard: CAN/CSA-C22.2 60079-0, CAN/CSA-E60079-11, CAN/CSA-E60079-15, CAN/CSA-C22.2 No.60529</p> <p>Ex ia IIC T4, Ex nL IIC T4 Enclosure: IP66/IP67</p> <p>Amb. Temp.: -50 to 60°C(-58 to 140°F) *3, Max. Process Temp.: 120°C(248°F)</p> <p>Electrical Parameters: [Ex ia] Ui=30V, li=200mA, Pi=0.9W, Ci=10nF, Li=0 µH</p> <p>[Ex nL] Ui=30V, Ci=10nF, Li=0 µH</p> <p>Process Sealing Certification</p> <p>Dual Seal Certified by CSA to the requirement of ANSI/ISA-12.27.01</p> <p>No additional sealing required</p> <p>Primary seal failure annunciation: at the zero adjustment screw</p> | CS1  |
|                                      | Combined CF1 and CS1 *1*2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | CU1  |

| Item                    | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Code |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| IECEX Scheme            | IECEx Flameproof Approval *1<br>Applicable Standard: IEC 60079-0, IEC 60079-1, IEC 60079-31<br>Certificate: IECEx DEK 14.0046X<br>Enclosure: IP66/IP67<br>Ex db IIC T6...T4 Gb, Ex tb IIIC T85°C Db<br>Amb. Temp. (Tamb) for gas-proof :<br>T4; -50 to 75°C (-58 to 167°F), T5; -50 to 80°C (-58 to 176°F), T6; -50 to 75°C (-58 to 167°F)<br>Process Temp. for gas-proof (Tp):<br>T4; -50 to 120°C (-58 to 248°F), T5; -50 to 100°C (-58 to 212°F),<br>T6; -50 to 85°C (-58 to 185°F)<br>Max. surface Temp. for dust-proof: T85°C (Tamb: -30 to 75°C, Tp: -30 to 85°C) *3                                                                                                | SF22 |
|                         | IECEx Intrinsically safe and SF22 *1*2<br>Intrinsically safe Ex ia<br>Certificate: IECEx DEK 11.0081X<br>Applicable Standard: IEC 60079-0, IEC 60079-11<br>Ex ia IIC T4 Ga Enclosure: IP66/IP67<br>Amb. Temp.: -50 to 60°C (-58 to 140°F), Max. Process Temp.: 120°C(248°F)<br>Electrical Parameters: Ui=30V, Ii=200mA, Pi=0.9W, Ci=27.6nF, Li=0 µH<br>Intrinsically safe Ex ic<br>Certificate: IECEx DEK 13.0061X<br>Applicable Standard: IEC 60079-0, IEC 60079-11<br>Ex ic IIC T4 Gc IP code: IP66<br>Amb. Temp.: -30 to 60°C (-22 to 140°F) *3, Max. Process Temp.: 120°C(248°F)<br>Electrical Parameters: Ui=30V, Ci=27.6 nF, Li=0 µH<br>Flameproof<br>Refer to SF22 | SU22 |
| Combination of Approval | Combination of KU22, FU1 and CU1 *1*2*4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | V1U1 |

\*1: Applicable for Electrical connection code 2, 4, 7, 9, C and D.

\*2: Not applicable for option code /AL.

\*3: Lower limit of temperature is -15°C (5°F) when /HE is specified.

\*4: When this option code is specified, a wired tag plate (as of N4 option) shall be used for tag number.

## ■ OPTIONAL SPECIFICATIONS

| Item                                                 |                | Description                                                                                                                                                                                                                                                                                 | Code                                                                                                 |     |    |
|------------------------------------------------------|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|-----|----|
| High Accuracy type <sup>*19</sup>                    |                | Reference accuracy: ±0.025% of Span                                                                                                                                                                                                                                                         | HAC                                                                                                  |     |    |
| Painting                                             | Color change   | Amplifier cover only <sup>*13</sup>                                                                                                                                                                                                                                                         | P□                                                                                                   |     |    |
|                                                      |                | Amplifier cover and terminal cover, Munsell 7.5 R4/14                                                                                                                                                                                                                                       | PR                                                                                                   |     |    |
|                                                      | Coating change | Anti-corrosion coating <sup>*1</sup>                                                                                                                                                                                                                                                        | X2                                                                                                   |     |    |
| 316 SST exterior parts                               |                | 316 SST zero-adjustment screw and setscrews <sup>*15</sup>                                                                                                                                                                                                                                  | HC                                                                                                   |     |    |
| Fluoro-rubber O-ring                                 |                | All O-rings of amplifier housing. Lower limit of ambient temperature: −15°C (5°F)                                                                                                                                                                                                           | HE                                                                                                   |     |    |
| Lightning protector                                  |                | Transmitter power supply voltage: 10.5 to 32 V DC ( 10.5 to 30 V DC for intrinsically safe type, 9 to 32 V DC for Fieldbus communication type.)<br>Allowable current: Max. 6000 A ( 1×40 μs ), Repeating 1000 A ( 1×40 μs ) 100 times<br>Applicable Standards: IEC 61000-4-4, IEC 61000-4-5 | A                                                                                                    |     |    |
| Status output <sup>*2</sup>                          |                | Transistor output (sink type)<br>Rating: 30 V DC, 120 mA DC (max) Low level: 0 to 2 V DC                                                                                                                                                                                                    | AL                                                                                                   |     |    |
| Oil-prohibited use                                   |                | Degrease cleansing treatment                                                                                                                                                                                                                                                                | K1                                                                                                   |     |    |
|                                                      |                | Degrease cleansing treatment and fluorinated oilfilled capsule.<br>Operating temperature −20 to 80°C (−4 to 176°F)                                                                                                                                                                          | K2                                                                                                   |     |    |
|                                                      |                | Degrease cleansing treatment                                                                                                                                                                                                                                                                | With certificates                                                                                    | K41 |    |
|                                                      |                | Degrease cleansing treatment and fluorinated oilfilled capsule.<br>Operating temperature −20 to 80°C (−4 to 176°F)                                                                                                                                                                          |                                                                                                      | K42 |    |
| Oil-prohibited use with dehydrating treatment        |                | Degrease cleansing and dehydrating treatment                                                                                                                                                                                                                                                | K5                                                                                                   |     |    |
|                                                      |                | Degrease cleansing and dehydrating treatment with fluorinated oilfilled capsule.<br>Operating temperature −20 to 80°C (−4 to 176°F)                                                                                                                                                         | K6                                                                                                   |     |    |
|                                                      |                | Degrease cleansing and dehydrating treatment                                                                                                                                                                                                                                                | With certificates                                                                                    | K45 |    |
|                                                      |                | Degrease cleansing and dehydrating treatment with fluorinated oilfilled capsule.<br>Operating temperature −20 to 80°C (−4 to 176°F)                                                                                                                                                         |                                                                                                      | K46 |    |
| Capsule fill fluid                                   |                | Flourinated oil filled in capsule<br>Operating temperature −20 to 80°C (−4 to 176°F)                                                                                                                                                                                                        | K3                                                                                                   |     |    |
| Calibration units <sup>*3</sup>                      |                | P calibration (psi unit)                                                                                                                                                                                                                                                                    | (See Table for Span and Range Limits.)                                                               | D1  |    |
|                                                      |                | bar calibration (bar unit)                                                                                                                                                                                                                                                                  |                                                                                                      | D3  |    |
|                                                      |                | M calibration (kgf/cm <sup>2</sup> unit)                                                                                                                                                                                                                                                    |                                                                                                      | D4  |    |
| Output limits and failure operation <sup>*4</sup>    |                | Failure alarm down-scale : Output status at CPU failure and hardware error is −5%, 3.2mA DC or less.                                                                                                                                                                                        |                                                                                                      | C1  |    |
|                                                      |                | NAMUR NE43 Compliant<br>Output signal limits:<br>3.8 mA to 20.5 mA                                                                                                                                                                                                                          | Failure alarm down-scale: Output status at CPU failure and hardware error is −5%, 3.2 mA DC or less. |     | C2 |
|                                                      |                |                                                                                                                                                                                                                                                                                             | Failure alarm up-scale: Output status at CPU failure and hardware error is 110%, 21.6 mA or more.    |     | C3 |
| Gold-plated diaphragm <sup>*18</sup>                 |                | Surface of isolating diaphragms are gold plated, effective for hydrogen permeation.                                                                                                                                                                                                         |                                                                                                      | A1  |    |
| Wired tag plate                                      |                | 316 SST tag plate wired onto transmitter                                                                                                                                                                                                                                                    |                                                                                                      | N4  |    |
| Data configuration at factory <sup>*5</sup>          |                | Data configuration for HART communication type                                                                                                                                                                                                                                              | Software damping, Descriptor, Message                                                                | CA  |    |
|                                                      |                | Data configuration for BRAIN communication type                                                                                                                                                                                                                                             | Software damping                                                                                     | CB  |    |
|                                                      |                | Data configuration for HART communication type                                                                                                                                                                                                                                              | Software damping, Descriptor, Message, External zero adjustment prohibition setting                  | CJ  |    |
|                                                      |                | Data configuration for BRAIN communication type                                                                                                                                                                                                                                             | Software damping, External zero adjustment prohibition setting                                       | CK  |    |
| Advanced diagnostics <sup>*16</sup>                  |                | Multi-sensing process monitoring<br>• Impulse line blockage detection <sup>*17</sup><br>• Heat trace monitoring                                                                                                                                                                             |                                                                                                      | DG6 |    |
| European Pressure Equipment Directive <sup>*14</sup> |                | PED 2014/68/EU<br>Category: III, Module: H, Type of Equipment: Pressure Accessory-Vessel, Type of Fluid: Liquid and Gas, Group of Fluid: 1 and 2                                                                                                                                            |                                                                                                      | PE3 |    |
| Material certificate <sup>*6</sup>                   |                | Process Connector                                                                                                                                                                                                                                                                           |                                                                                                      | M15 |    |
|                                                      |                | Process connector, Diaphragm, Capsule body                                                                                                                                                                                                                                                  |                                                                                                      | MA2 |    |



|                                            |                                                                                                           |            |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------|------------|
| Calibration certificate                    | Text, Traceability                                                                                        | <b>L4</b>  |
|                                            | Text, Traceability, Primary standards list                                                                | <b>L5</b>  |
|                                            | Text, Traceability, Primary standards list, Calibration equipment list                                    | <b>L6</b>  |
|                                            | Text, Traceability, Primary standards list, Calibration equipment list, Calibration equipment certificate | <b>L9</b>  |
| Pressure test/<br>Leak test certificate*12 | Test Pressure: 200 kPa (29 psi) *7                                                                        | <b>T05</b> |
|                                            | Test Pressure: 2 MPa (290 psi) *8                                                                         | <b>T06</b> |
|                                            | Test Pressure: 10 MPa (1450 psi) *9                                                                       | <b>T07</b> |
|                                            | Test Pressure: 70 MPa (10150 psi) *10                                                                     | <b>T15</b> |
| Parameter list*22                          | List of setting and adjustment parameters                                                                 | <b>YP</b>  |
| Additional blind plug*23                   | Additional blind plug is attached to the conduit connection on both sides for storing transmitter         | <b>PP</b>  |
| Functional safety(SIL)*20*21               | Low temperature expansion of functional safety Amb.Temp.: -55 to 85°C                                     | <b>SLT</b> |

- \*1: Not applicable with color change option.
- \*2: Check/External indicator terminals cannot be used when this option code is specified. Not applicable for output signal code F and G.
- \*3: The unit of MWP (Max. working pressure) on the name plate of a housing is the same unit as specified by option codes D1, D3, and D4.
- \*4: Applicable for output signal codes D, E and J. The hardware error indicates faulty amplifier or capsule.
- \*5: Also see 'Ordering Information'.
- \*6: Material traceability certification, per EN 10204 3.1 B.
- \*7: Applicable for capsule code A.
- \*8: Applicable for capsule code B.
- \*9: Applicable for capsule code C.
- \*10: Applicable for capsule code D.
- \*11: Dry nitrogen gas or pure water is used for oil-prohibited use (option codes K1, K2, K5, K6, K41, K42, K45, and K46).
- \*12: The unit on the certificate is always kPa/MPa regardless of selection of option code D1, D3 and D4.
- \*13: Not applicable for amplifier housing code 2 and 3.
- \*14: Applicable for measurement span code D. If compliance with category III is needed, specify this option code.
- \*15: 316 or 316L SST. The specification is included in amplifier code 2.
- \*16: Applicable only for output signal code E and J.
- \*17: The change of pressure fluctuation is monitored and then detects the impulse line blockage. See TI 01C25A31-01E for detailed technical information required for using this function.
- \*18: Applicable for wetted parts material code S.
- \*19: Refer to "PERFORMANCE SPECIFICATIONS". Applicable only for EJX630A.  
Not applicable for the combination of measurement span code A and wetted parts material code H. Not applicable for option code K2, K3 or A1. When specified range values include negative value for A capsule, the accuracy shall be the standard accuracy even if high accuracy option (HAC) is specified.
- \*20: Not applicable for EJX610A.
- \*21: Not applicable for output signal code F, G, P and S.
- \*22: Applicable only for output signal code D, E and J.
- \*23: Not applicable for electrical connection codes 0, 2, and 4.