



# CODE SYMBOLS

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16																																																												
F	K	E					F									DESCRIPTION																																																											
																<b>Type</b> Smart, 4-20 mAdc + Fuji/Hart® digital signal																																																											
																<b>Connections</b> <table border="1"> <tr> <th colspan="2">LP side connections</th> <th>Electric. housing</th> </tr> <tr> <th>Process</th> <th>Oval flange screw</th> <th>Conduit connection</th> </tr> <tr> <td>1/4-18 NPT</td> <td>7/16-20 UNF</td> <td>M 20 x 1,5</td> </tr> <tr> <td>1/4-18 NPT</td> <td>7/16-20 UNF</td> <td>1/2-14 NPT</td> </tr> <tr> <td>1/4-18 NPT</td> <td>M10</td> <td>Pg 13,5</td> </tr> <tr> <td>1/4-18 NPT</td> <td>M10</td> <td>M 20 x 1,5</td> </tr> <tr> <td>1/4-18 NPT</td> <td>7/16-20 UNF</td> <td>Pg 13,5</td> </tr> </table>	LP side connections		Electric. housing	Process	Oval flange screw	Conduit connection	1/4-18 NPT	7/16-20 UNF	M 20 x 1,5	1/4-18 NPT	7/16-20 UNF	1/2-14 NPT	1/4-18 NPT	M10	Pg 13,5	1/4-18 NPT	M10	M 20 x 1,5	1/4-18 NPT	7/16-20 UNF	Pg 13,5																																						
LP side connections		Electric. housing																																																																									
Process	Oval flange screw	Conduit connection																																																																									
1/4-18 NPT	7/16-20 UNF	M 20 x 1,5																																																																									
1/4-18 NPT	7/16-20 UNF	1/2-14 NPT																																																																									
1/4-18 NPT	M10	Pg 13,5																																																																									
1/4-18 NPT	M10	M 20 x 1,5																																																																									
1/4-18 NPT	7/16-20 UNF	Pg 13,5																																																																									
R																<b>Mounting flange</b> <table border="1"> <tr> <th>Material</th> <th>Size and rating</th> <th>Flange mount. position</th> </tr> <tr> <td rowspan="4">SS 316 L</td> <td>ANSI-150LB3"-ISO PN 20 DN 80</td> <td rowspan="4">Long design</td> </tr> <tr> <td>ANSI-150LB4"-ISO PN 20 DN 100</td> </tr> <tr> <td>DIN PN40 DN80</td> </tr> <tr> <td>DIN PN16 DN100</td> </tr> <tr> <td rowspan="4"></td> <td>ANSI-150LB3"-ISO PN 20 DN 80</td> <td rowspan="4">Short design</td> </tr> <tr> <td>ANSI-150LB4"-ISO PN 20 DN 100</td> </tr> <tr> <td>DIN PN40 DN80</td> </tr> <tr> <td>DIN PN16 DN100</td> </tr> </table>	Material	Size and rating	Flange mount. position	SS 316 L	ANSI-150LB3"-ISO PN 20 DN 80	Long design	ANSI-150LB4"-ISO PN 20 DN 100	DIN PN40 DN80	DIN PN16 DN100		ANSI-150LB3"-ISO PN 20 DN 80	Short design	ANSI-150LB4"-ISO PN 20 DN 100	DIN PN40 DN80	DIN PN16 DN100																																												
Material	Size and rating	Flange mount. position																																																																									
SS 316 L	ANSI-150LB3"-ISO PN 20 DN 80	Long design																																																																									
	ANSI-150LB4"-ISO PN 20 DN 100																																																																										
	DIN PN40 DN80																																																																										
	DIN PN16 DN100																																																																										
	ANSI-150LB3"-ISO PN 20 DN 80	Short design																																																																									
	ANSI-150LB4"-ISO PN 20 DN 100																																																																										
	DIN PN40 DN80																																																																										
	DIN PN16 DN100																																																																										
4																<b>Measuring range (mmH2O)</b> <table border="1"> <tr> <td>(*)</td> <td>10</td> <td>600</td> </tr> <tr> <td>(*)</td> <td>32</td> <td>3200</td> </tr> <tr> <td></td> <td>130</td> <td>13000</td> </tr> <tr> <td></td> <td>500</td> <td>50000</td> </tr> <tr> <td></td> <td>3000</td> <td>300000</td> </tr> </table>	(*)	10	600	(*)	32	3200		130	13000		500	50000		3000	300000																																												
(*)	10	600																																																																									
(*)	32	3200																																																																									
	130	13000																																																																									
	500	50000																																																																									
	3000	300000																																																																									
5																<b>Material</b> <table border="1"> <tr> <th rowspan="2"></th> <th colspan="2">LP side</th> <th colspan="2">HP side</th> </tr> <tr> <th>Process cover</th> <th>Diaphragm</th> <th>Wetted sensor body</th> <th>Diaphragm and flange face</th> </tr> <tr> <td>V</td> <td>SS 316</td> <td>SS 316L</td> <td>SS 316</td> <td>SS 316 L</td> </tr> <tr> <td>W</td> <td>(*) SS 316</td> <td>Hastelloy-C</td> <td>SS 316</td> <td>Hastelloy-C</td> </tr> <tr> <td>H</td> <td>(*) SS 316</td> <td>SS 316L</td> <td>SS 316</td> <td>Hastelloy-C</td> </tr> <tr> <td>M</td> <td>(*) SS 316</td> <td>SS 316L</td> <td>SS 316</td> <td>Monel</td> </tr> <tr> <td>T</td> <td>(*) SS 316</td> <td>SS 316L</td> <td>SS 316</td> <td>Tantalum</td> </tr> <tr> <td>A</td> <td>(*) SS 316</td> <td>SS 316L</td> <td>SS 316</td> <td>SS 316L + FEP lining</td> </tr> <tr> <td>K</td> <td>(*) SS 316</td> <td>SS 316L</td> <td>SS 316</td> <td>SS 316L + glued PTFE diaphragm</td> </tr> <tr> <td>B</td> <td>(*) SS 316</td> <td>SS 316L</td> <td>SS 316</td> <td>SS 316L + gold coat</td> </tr> <tr> <td>P</td> <td>(*) SS 316</td> <td>SS 316L</td> <td>SS 316</td> <td>Titanium</td> </tr> <tr> <td>R</td> <td>(*) SS 316</td> <td>SS 316L</td> <td>SS 316</td> <td>Zirconium</td> </tr> </table>		LP side		HP side		Process cover	Diaphragm	Wetted sensor body	Diaphragm and flange face	V	SS 316	SS 316L	SS 316	SS 316 L	W	(*) SS 316	Hastelloy-C	SS 316	Hastelloy-C	H	(*) SS 316	SS 316L	SS 316	Hastelloy-C	M	(*) SS 316	SS 316L	SS 316	Monel	T	(*) SS 316	SS 316L	SS 316	Tantalum	A	(*) SS 316	SS 316L	SS 316	SS 316L + FEP lining	K	(*) SS 316	SS 316L	SS 316	SS 316L + glued PTFE diaphragm	B	(*) SS 316	SS 316L	SS 316	SS 316L + gold coat	P	(*) SS 316	SS 316L	SS 316	Titanium	R	(*) SS 316	SS 316L	SS 316	Zirconium
	LP side		HP side																																																																								
	Process cover	Diaphragm	Wetted sensor body	Diaphragm and flange face																																																																							
V	SS 316	SS 316L	SS 316	SS 316 L																																																																							
W	(*) SS 316	Hastelloy-C	SS 316	Hastelloy-C																																																																							
H	(*) SS 316	SS 316L	SS 316	Hastelloy-C																																																																							
M	(*) SS 316	SS 316L	SS 316	Monel																																																																							
T	(*) SS 316	SS 316L	SS 316	Tantalum																																																																							
A	(*) SS 316	SS 316L	SS 316	SS 316L + FEP lining																																																																							
K	(*) SS 316	SS 316L	SS 316	SS 316L + glued PTFE diaphragm																																																																							
B	(*) SS 316	SS 316L	SS 316	SS 316L + gold coat																																																																							
P	(*) SS 316	SS 316L	SS 316	Titanium																																																																							
R	(*) SS 316	SS 316L	SS 316	Zirconium																																																																							
F	-	A														<b>Indicator and arrester</b> <table border="1"> <tr> <th>Indicator</th> <th>Arrester</th> <th>Initial setting</th> </tr> <tr> <td>None</td> <td>None</td> <td></td> </tr> <tr> <td>Analog, 0 to 100% linear scale</td> <td>None</td> <td></td> </tr> <tr> <td>Analog, custom scale</td> <td>None</td> <td></td> </tr> <tr> <td>Analog, double scale</td> <td>None</td> <td>4-20mA DC</td> </tr> <tr> <td>None</td> <td>Yes</td> <td>+</td> </tr> <tr> <td>Analog, 0 to 100% linear scale</td> <td>Yes</td> <td>Hart®/Fuji</td> </tr> <tr> <td>Analog, custom scale</td> <td>Yes</td> <td>digital signal</td> </tr> <tr> <td>Analog, double scale</td> <td>Yes</td> <td>"SMART"</td> </tr> <tr> <td>Digital, 0 to 100%</td> <td>None</td> <td></td> </tr> <tr> <td>Digital, custom scale</td> <td>None</td> <td></td> </tr> <tr> <td>Digital, 0 to 100%</td> <td>Yes</td> <td></td> </tr> <tr> <td>Digital, custom scale</td> <td>Yes</td> <td></td> </tr> </table>	Indicator	Arrester	Initial setting	None	None		Analog, 0 to 100% linear scale	None		Analog, custom scale	None		Analog, double scale	None	4-20mA DC	None	Yes	+	Analog, 0 to 100% linear scale	Yes	Hart®/Fuji	Analog, custom scale	Yes	digital signal	Analog, double scale	Yes	"SMART"	Digital, 0 to 100%	None		Digital, custom scale	None		Digital, 0 to 100%	Yes		Digital, custom scale	Yes																					
Indicator	Arrester	Initial setting																																																																									
None	None																																																																										
Analog, 0 to 100% linear scale	None																																																																										
Analog, custom scale	None																																																																										
Analog, double scale	None	4-20mA DC																																																																									
None	Yes	+																																																																									
Analog, 0 to 100% linear scale	Yes	Hart®/Fuji																																																																									
Analog, custom scale	Yes	digital signal																																																																									
Analog, double scale	Yes	"SMART"																																																																									
Digital, 0 to 100%	None																																																																										
Digital, custom scale	None																																																																										
Digital, 0 to 100%	Yes																																																																										
Digital, custom scale	Yes																																																																										
A																<b>Approvals for hazardous locations (consult FUJI for availability)</b> None (Standard) ATEX - Flameproof enclosures (digit 4 = "M, P, R, T" & "W" only) ATEX - Intrinsic Safety (*6) FM - Explosion-Proof (digit 4 = "P" & "T" only) CSA - Explosion-Proof (digit 4 = "P" & "T" only) FM - Intrinsic Safety and Non Incendive CSA - Intrinsic Safety ATEX - Type "n" (digit 9 = A, E, 1, 2, 3, 4, 5 & 6 only) IECEx - Type "n" (digit 9 = A, E, 1, 2, 3, 4, 5 & 6 only) IECEx - Flameproof enclosures (digit 4 = "M, P, R, T" & "W" only) IECEx - Intrinsic Safety CSA - Explosion-Proof & Intrinsic Safety combined approval (digit 4 = "P" & "T" only) ATEX - Flameproof enclosures & Intrinsic Safety combined approval (digit 4 = "M, P, R, T" & "W" only) IECEx - Flameproof enclosures & Intrinsic Safety combined approval (digit 4 = "M, P, R, T" & "W" only) FM - Explosion-Proof & Intrinsic Safety combined approval (digit 4 = "P" & "T" only)																																																											
Y																<b>Diaphragm extension (mm)</b> <table border="1"> <tr> <th>Extension (mm)</th> <th>Applicable material code</th> </tr> <tr> <td>0</td> <td>Any</td> </tr> <tr> <td>(*) 50</td> <td rowspan="4">Material code "V"</td> </tr> <tr> <td>(*) 100</td> </tr> <tr> <td>(*) 150</td> </tr> <tr> <td>(*) 200</td> </tr> <tr> <td>(*) 50</td> <td rowspan="4">Material code "H"</td> </tr> <tr> <td>(*) 100</td> </tr> <tr> <td>(*) 150</td> </tr> <tr> <td>(*) 200</td> </tr> <tr> <td>(*) 50</td> <td rowspan="4">Material code "M"</td> </tr> <tr> <td>(*) 100</td> </tr> <tr> <td>(*) 150</td> </tr> <tr> <td>(*) 200</td> </tr> <tr> <td>(*) 50</td> <td rowspan="4">Material code "T"</td> </tr> <tr> <td>(*) 100</td> </tr> <tr> <td>(*) 150</td> </tr> <tr> <td>(*) 200</td> </tr> </table>	Extension (mm)	Applicable material code	0	Any	(*) 50	Material code "V"	(*) 100	(*) 150	(*) 200	(*) 50	Material code "H"	(*) 100	(*) 150	(*) 200	(*) 50	Material code "M"	(*) 100	(*) 150	(*) 200	(*) 50	Material code "T"	(*) 100	(*) 150	(*) 200																																			
Extension (mm)	Applicable material code																																																																										
0	Any																																																																										
(*) 50	Material code "V"																																																																										
(*) 100																																																																											
(*) 150																																																																											
(*) 200																																																																											
(*) 50	Material code "H"																																																																										
(*) 100																																																																											
(*) 150																																																																											
(*) 200																																																																											
(*) 50	Material code "M"																																																																										
(*) 100																																																																											
(*) 150																																																																											
(*) 200																																																																											
(*) 50	Material code "T"																																																																										
(*) 100																																																																											
(*) 150																																																																											
(*) 200																																																																											

Notes\* :

- Turn down of 100 : 1 is possible, but it should be used at a span greater than 1/40 of the maximum span for better performance.
- Add values for material options are for DN80 PN40 or ANSI-150 LB3" flange rate, DN100 or 4" add values are available upon request, LP side writed cell body diaphragm in exotic materials are available upon request.
- All wetted parts in the same material (diaphragm, extension, flange gasket area)
- When no code can be found in the current code symbols, place\* in concerned code digit(s) & add\* in 16 th digit
- Our stainless steel bolts/nuts in SS660 are in conformity with the NACE requirements and must be used for NACE service
- Code "D & V" FM approval only possible with electrical connection 1/2" NPT.
- Please consult Fuji with you application conditions

