

Note: For a shorter delivery time, order commonly stocked probes. Currently, stocked probes consist of the following part numbers: 330701-00-10-10-02-00, 330701-00-20-10-02-00, 330703-000-050-10-02-00, 330705-02-18-10-02-00, 330706-005-046-10-02-00.

3300 XL 11 mm Proximator Sensor

330780-AXX-BXX

Option Descriptions

A: Total Length and Mounting Option

- 5 0** 5.0 metre (16.4 feet) system length, panel mount
- 5 1** 5.0 metre (16.4 feet) system length, DIN mount
- 5 2** 5.0 metre (16.4 feet) system length, no mounting hardware
- 9 0** 9.0 metres (29.5 feet) system length, panel mount
- 9 1** 9.0 metres (29.5 feet) system length, DIN mount
- 9 2** 9.0 metres (29.5 feet) system length, no mounting hardware

B: Agency Approval Option

- 0 0** Not required
- 0 5** Multiple approvals

3300 XL 11 mm Extension Cable

330730-AXXX-BXX-CXX

Note: Make sure that the extension cable length and the probe length, when added together, equal the Proximator Sensor total length.

Option Descriptions

A: Cable Length Option

- 0 4 0** 4.0 metres (13.1 feet)
- 0 8 0** 8.0 metres (26.2 feet)

B: Connector and Cable Option

- 0 0** Standard cable
- 0 1** Armored cable
- 0 2** Standard cable with connector protectors
- 0 3** Armored cable with connector protectors
- 1 0** FluidLoc cable
- 1 1** Armored FluidLoc cable
- 1 2** FluidLoc cable with connector protectors
- 1 3** Armored FluidLoc cable with connector protectors

C: Agency Approval Option

- 0 0** Not required
- 0 5** Multiple Approvals

Accessories

146255-01

Manual

144979

Performance Specification

02120015

Bulk field wire. 1.0 mm² (18 AWG), 3 conductor, twisted, shielded cable with drain wire. Specify length in feet.

02173009

Bulk field wire. 1.0 mm² (18 AWG), 3 conductor, twisted, shielded cable. Specify length in feet.

138492-01

Replacement panel-mount mounting pad

138493-01

Replacement DIN-mount mounting pad

01609137

BNC (F) to banana plugs

01609138

Proximator Connector Test Pin wiring (two test pins to a BNC (F) connector)

40971-04

50 Ω cable with two BNC (M) connectors. Use this cable in combination with adapter 01609137 and adapter 01609138 when checking performance of the transducer system from the Proximator Sensor test pin holes.

04310310

3300 XL Proximator Sensor Panel-mount Screws. Package includes four 6-32 UNC thread forming mounting screws (Supplied standard with 3300 XL Proximator Housings [3300 XL option]).

03200006

Silicone self-fusing tape. A 9.1 metre (10 yard) roll of silicone tape to protect connectors. It is easy to install and provides excellent electrical isolation and protection from the environment. It is not recommended for use inside the casing of the machine.

40113-02

Connector Protector Kit.
Connector Protector Kit for 3300 XL probes and extension cables, including connector protectors and installation tools.

136536-01

Connector Protector Adapter.
Makes our previous 3300 connector protector kits compatible with 3300 XL probes and extension cable connectors.

40180-02

Connector Protectors. Package contains 10 pairs of connector protectors.

03839410

Male Connector Protector.
Placed on the extension cable to connect to the female connector protector on the probe and provide environmental protection of connectors.

03839420

Female Connector Protector.
Placed on the probe lead to connect to the male connector protector on the extension cable and provide environmental protection of connectors. Also placed on the extension cable to slide over the Proximitor Sensor connection and protect it from the environment.

330153-01

3300 XL Connector Kit. Used on 3300 XL probes and extension cables. Contains one set of male and female ClickLoc connectors, sleeves and one strip of silicone tape.

163356

Connector Crimp Tool Kit.
Includes one set of 75 Ω 3300 XL ClickLoc inserts and connector installation instructions. Supplied with carrying case.